

60V N-Channel Enhancement Mode MOSFET

1.Product Information

1.1 Features

- ◇ Advanced TRENCH cell design
- ◇ Low Gate Charge
- ◇ Low On-Resistance
- ◇ RoHS and Halogen-Free Compliant
- ◇ 100% ΔV_{DS} & UIS & R_g Tested

1.2 Applications



- ◇ DC-DC Converter
- ◇ Drones
- ◇ Motor drivers
- ◇ Light electric vehicles

1.3 Quick reference

- ◇ $BV \cong 60\text{ V}$
- ◇ $P_{\text{tot}} \cong 517\text{ W}$
- ◇ $I_D \cong 334\text{ A}$
- ◇ $R_{DS(ON)} \cong 2.2\text{ m}\Omega @ V_{GS} = 10\text{ V}$
- ◇ $R_{DS(ON)} \cong 3.0\text{ m}\Omega @ V_{GS} = 6\text{ V}$



2.Pin Description



3.Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit	Note
V_{DS}	Drain-Source Voltage	$T_C = 25\text{ }^{\circ}\text{C}$	-	60	V	-
V_{GS}	Gate-Source Voltage	$T_C = 25\text{ }^{\circ}\text{C}$	-	± 20	V	-
I_D^*	Drain Current (DC)	$T_C = 25\text{ }^{\circ}\text{C}, V_{GS} = 10\text{ V}$	-	334	A	Fig.2
		$T_C = 100\text{ }^{\circ}\text{C}, V_{GS} = 10\text{ V}$	-	236	A	
$I_{DM}^{**},^{***}$	Drain Current (Pulsed)	$T_C = 25\text{ }^{\circ}\text{C}, V_{GS} = 10\text{ V}$	-	509	A	-
P_{tot}	Drain power dissipation	$T_C = 25\text{ }^{\circ}\text{C}$	-	517	W	Fig.1
		$T_C = 100\text{ }^{\circ}\text{C}$	-	258	W	
	Linear reduction	$T_A > 25\text{ }^{\circ}\text{C}$	-	3.44	W/ $^{\circ}\text{C}$	
T_{stg}	Storage Temperature		-55	175	$^{\circ}\text{C}$	-
T_J	Junction Temperature		-	175	$^{\circ}\text{C}$	-
I_S	Continuous-Source Current	$T_C = 25\text{ }^{\circ}\text{C}$	-	334	A	-
E_{AS}^*	Single Pulsed Avalanche Energy	$V_{DD} = 60\text{ V}, L = 0.5\text{ mH}$	-	1255	mJ	Fig.19

4.Thermal Characteristics

$R_{\theta JA}^*$	Thermal Resistance- Junction to Ambient	-	14	$^{\circ}\text{C/W}$	Fig.16
$R_{\theta JC}^*$	Thermal Resistance- Junction to Case	-	0.29		

Notes :

- * Surface Mounted on 1 in² pad area, $t \leq 10\text{ sec}$
- ** Pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$
- *** limited by bonding wire

5.Marking Information

Product Name	Package	Reel size	Tape width	Quantity	Note
LN018N060T-H	TOLL	330mm	24mm	2000	

Note: COMTECH defines “ Green ” as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC / JEDEC J-STD-020C)

6. Electrical Characteristics ($T_A=25^\circ$ Unless Otherwise Noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit	Note
Static Characteristics							
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0 V, I _{DS} = 250 μA	60	-	-	V	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _{DS} = 250 μA	2	-	4	V	
I _{DSS}	Drain Leakage Current	V _{DS} = 60 V, V _{GS} = 0 V	-	-	1	μA	
I _{GSS}	Gate Leakage Current	V _{GS} = ± 20 V, V _{DS} = 0 V	-	-	±100	nA	
R _{DS(ON)} ^a	On-State Resistance	V _{GS} = 10 V, I _{DS} = 30 A	-	1.9	2.2	mΩ	Fig.8
		V _{GS} = 6 V, I _{DS} = 20 A	-	2.5	3.0		
Diode Characteristics							
V _{SD} ^a	Diode Forward Voltage	I _{SD} = 30 A, V _{GS} = 0 V	-	-	1.3	V	Fig.7
t _{rr}	Reverse Recovery Time	I _{DS} = 30 A, V _{GS} = 0 V dI _{SD} /dt = 100 A/μs	-	35	-	nS	Fig.20
Q _{rr}	Reverse Recovery Charge		-	125	-	nC	
Dynamic Characteristics ^b							
C _{iss}	Input Capacitance	V _{GS} = 0 V, V _{DS} = 30 V Frequency = 1 MHz	-	13000	-	pF	Fig.10
C _{oss}	Output Capacitance		-	490	-		
C _{rss}	Reverse Transfer Capacitance		-	477	-		
R _G	Gate Resistance	F= 1 MHz	-	1.6	-	Ω	
t _{d(on)}	Turn-on Delay Time	V _{DS} = 30 V, V _{GS} = 10 V, R _G =2.7 Ω, R _L = 10 uH, I _{DS} = 30 A	-	48	-	nS	Fig.18
t _r	Turn-on Rise Time		-	111	-		
t _{d(off)}	Turn-off Delay Time		-	117	-		
t _f	Turn-off Fall Time		-	37	-		
dv/dt	Peak Diode Recovery		-	0.217	-	KV/us	
di/dt	Peak Diode Recovery		-	404	-	A/us	
Gate Charge Characteristics ^b							
Q _g	Total Gate Charge	V _{DS} = 30 V, V _{GS} = 10 V, I _{DS} = 30 A	-	224	-	nC	Fig.9
Q _{gs}	Gate-Source Charge		-	54	-		
Q _{gd}	Gate-Drain Charge		-	59	-		
V _{plateau}	Gate plateau voltage		-	4.4	-	V	

Notes :

a : Pulse test ; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$

b : Guaranteed by design, not subject to production testing

7. Typical Characteristics

Fig.1 Power Capability




Fig.2 Current Capability




Fig.3 Output Characteristics@ $T_j -55^\circ\text{C}$





Fig.4 Output Characteristics@ $T_j 25^\circ\text{C}$



7. Typical Characteristics

Fig.5 Output Characteristics@T_j 175°C




Fig.6 Transfer Characteristics vs Temp




Fig.7 Body Diode Characteristics





Fig.8 Drain-Source On Resistance



7. Typical Characteristics

Fig.9 Gate Charge




Fig.10 Capacitance




Fig.11 Normalized Threshold Voltage





Fig.12 Normalized Breakdown Voltage



7. Typical Characteristics

Fig.13 Normalized On Resistance




Fig.14 Switching Energy vs I_D




Fig.15 Safe Operating Area





Fig.16 Transient Thermal Impedance



7. Typical Characteristics

Fig.17 Gate Charge Test Circuit & Waveform




Fig.18 Resistive Switching Test Circuit & Waveforms




Fig.19 Unclamped Inductive Switching (UIS) Test Circuit & Waveforms






Fig.20 Diode Recovery Test Circuit & Waveforms



8. Package Dimensions

TOLL Package



Symbol	Dimensions In Millimeters		
	MIN.	NOM.	MAX.
A	2.20	2.30	2.40
b	0.70	0.80	0.90
b1	9.70	9.80	9.90
b2	0.36	0.45	0.55
b3	0.05	0.10	0.35
b4	0.30	0.40	0.50
b5	1.10	1.20	1.30
b6	3.00	3.10	3.20
c	0.40	0.50	0.60
D	10.28	10.38	10.55
D1	10.98	11.08	11.18
D2	3.20	3.30	3.40
D3	7.00	7.15	7.30
D4	3.44	3.59	3.74
e	1.10	1.20	1.30
E	9.80	9.90	10.00
E1	8.20	8.30	8.40
E2	8.35	8.50	8.65
H	11.50	11.68	11.85
K	4.08	4.18	4.28
K1	2.45	-	-
L	1.60	1.90	2.10
L1	0.50	0.70	0.90
L2	0.50	0.60	0.70
L3	1.00	1.20	1.30
L4	0.13	0.23	0.33
P	2.85	3.00	3.15
θ	10°REF.		
aaa	0.20		
ccc	0.20		
ddd	0.25		
eee	0.20		

9. Record of Document amendment

产品名称：LN018N060T-H
版权说明：镭诺电子（宁波）有限公司
联系电话：4008887385

文档类型：产品手册
公司主页：www.leinuosemi.com

版本：01
修改记录：
1.初版发行