

150V N-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ◇ Surface-mounted package
- ◇ Advanced SGT cell design
- ◇ Tj max 175°C
- ◇ MSL1



1.2 Applications

- ◇ Power Tool appliances
- ◇ BMS appliances
- ◇ High power inverter system

1.3 Quick reference

- ◇ BV \cong 150 V
- ◇ P_{tot} \cong 375 W
- ◇ I_D \cong 220 A
- ◇ R_{DS(ON)} \cong 5.0m Ω @ V_{GS} = 10 V
- ◇ R_{DS(ON)} \cong 6.0m Ω @ V_{GS} = 6 V

2. Pin Description



3. Marking Information

Product Name	Marking
LN050N150T	LN050N150T AYWWZZ XXXXXX

4.Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	$T_C = 25\text{ }^\circ\text{C}$	-	150	V
V_{GS}	Gate-Source Voltage	$T_C = 25\text{ }^\circ\text{C}$	-	± 25	V
I_D^*	Drain Current (DC)	$T_C = 25\text{ }^\circ\text{C}, V_{GS} = 10\text{ V}$	-	220	A
		$T_C = 100\text{ }^\circ\text{C}, V_{GS} = 10\text{ V}$	-	103	A
I_{DM}^*	Drain Current (Pulsed)	$T_C = 25\text{ }^\circ\text{C}, V_{GS} = 10\text{ V}$	-	584	A
P_{tot}	Drain power dissipation	$T_C = 25\text{ }^\circ\text{C}$	-	288	W
T_{stg}	Storage Temperature		-55	175	$^\circ\text{C}$
T_J	Junction Temperature		-	175	$^\circ\text{C}$
I_S	Continuous-Source Current	$T_C = 25\text{ }^\circ\text{C}$	-	220	A
I_{AS}	Single Pulsed Avalanche Current	$V_{DD} = 100\text{ V}, L = 0.05\text{ mH}$	-	160	A
E_{AS}	Single Pulsed Avalanche Energy	$V_{DD} = 100\text{ V}, L = 1.0\text{ mH}$	-	1250	mJ
R_{AS}	Thermal Resistance- Junction to Ambient		-	40	$^\circ\text{C/W}$
$R_{\theta JA}^{**}$	Thermal Resistance- Junction to Case			0.52	

Notes :

* Surface Mounted on minimum footprint pad area.

** Pulse width $\leq 300\text{ s}$, duty cycle $\leq 2\%$

*** Maximum current rating is package limited.

5.Ordering Code

Product Name	Package	Reel Size	Tape width	Quantity	Note
LN050N150T	TOLL-8			2000	

Note: COMTECH defines " Green " as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC / JEDEC J-STD-020C)

6. Electrical Characteristics (TA=25 ° Unless Otherwise Noted)





Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_{DS} = 250\ \mu\text{A}$	150	-	-	V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_{DS} = 250\ \mu\text{A}$	2	-	4	V
I_{DSS}	Drain Leakage Current	$V_{DS} = 120\text{ V}, V_{GS} = 0\text{ V}$	-	-	1	μA
I_{GSS}	Gate Leakage Current	$V_{GS} = 0\text{ V}, V_{GS} = \pm 25\text{ V}$	-	-	± 100	nA
$R_{DS(on)}^a$	On-State Resistance	$V_{GS} = 10\text{ V}, I_{DS} = 50\text{ A}$	-	4.5	5.0	m Ω
		$V_{GS} = 6\text{ V}, I_{DS} = 25\text{ A}$	-	5.0	6.0	
Diode Characteristics						
V_{SD}^a	Diode Forward Voltage	$I_{SD} = 50\text{ A}, V_{GS} = 0\text{ V}$	-	-	1.3	V
t_{rr}	Reverse Recovery Time	$I_{DS} = 50\text{ A}, V_{GS} = 0\text{ V}$	-	115	-	nS
Q_{rr}	Reverse Recovery Charge	$dI_{SD}/dt = 100\text{ A}/\mu\text{s}$	-	480	-	nC
Dynamic Characteristics^b						
C_{ISS}	Input Capacitance	$V_{GS} = 0\text{ V}, V_{DS} = 75\text{ V}$ Frequency = 1 MHz	-	9320	-	pF
C_{OSS}	Output Capacitance		-	570	-	
C_{rSS}	Reverse Transfer Capacitance		-	60	-	
$t_d(on)$	Turn-on Delay Time	$V_{DS} = 75\text{ V}, V_{GEN} = 10\text{ V},$ $R_G = 3.9\ \Omega, R_L = 1.5\ \Omega,$ $I_{DS} = 50\text{ A}$	-	24	-	nS
t_r	Turn-on Rise Time		-	70	-	
$t_d(off)$	Turn-off Delay Time		-	112	-	
t_f	Turn-off Fall Time		-	75	-	
Gate Charge Characteristics^b						
Q_g	Total Gate Charge	$V_{DS} = 75\text{ V}, V_{GS} = 10\text{ V},$ $I_{DS} = 50\text{ A}$	-	158	-	nC
Q_{gs}	Gate-Source Charge		-	48	-	
Q_{gd}	Gate-Drain Charge		-	39	-	

Notes :





a : Pulse test ; pulse width $\leq 300\ \mu\text{s}$, duty cycle $\leq 2\%$

b : Guaranteed by design, not subject to production testing





7. Typical Characteristics



7. Typical Characteristics (cont.)




7. Typical Characteristics (cont.)



8. Package Dimensions

TOLL-8 Package



Symbol	Dimensions In Millimeters	
	Min.	Max.
A	2.20	2.40
b	0.70	0.90
b1	9.70	9.90
b2	0.42	0.50
c	0.40	0.60
D	10.28	10.58
D2	3.10	3.50
E	9.70	10.10
E1	7.90	8.30
e	1.20BSC	
H	11.48	11.88
H1	6.75	7.15
N	8	
J	3.00	3.30
K1	3.98	4.38
L	1.40	1.80
L1	0.60	0.80
L2	0.50	0.70
L4	1.00	1.30
θ	4°	10°