

## 200V N-Channel Enhancement Mode MOSFET

### 1. Product Information

#### 1.1 Features

- ◇ Surface-mounted package
- ◇ Advanced SGT cell design



#### 1.2 Applications

- ◇ MB and NB
- ◇ TV and Monitor
- ◇ DC to DC Converter
- ◇ LCD Inverter

#### 1.3 Quick reference

- ◇  $BV \cong 200\text{ V}$
- ◇  $P_{\text{tot}} \cong 24\text{ W}$
- ◇  $I_D \cong 6\text{ A}$
- ◇  $R_{\text{DS(ON)}} \cong 430\text{ m}\Omega @ V_{\text{GS}} = 10\text{ V}$
- ◇  $R_{\text{DS(ON)}} \cong 520\text{ m}\Omega @ V_{\text{GS}} = 6\text{ V}$

### 2. Pin Description



### 3. Marking Information

Product Name	Marking
LN3R88N200J	LN3R88N200J CYWWZZ XXXXXX

## 4. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
$V_{DS}$	Drain-Source Voltage	$T_C = 25\text{ }^\circ\text{C}$	-	200	V
$V_{GS}$	Gate-Source Voltage	$T_C = 25\text{ }^\circ\text{C}$	-	$\pm 20$	V
$I_D$	Drain Current ( DC )	$T_C = 25\text{ }^\circ\text{C}, V_{GS} = 10\text{ V}$	-	6	A
		$T_C = 100\text{ }^\circ\text{C}, V_{GS} = 10\text{ V}$	-	2.8	A
$I_{DM}^{**}$	Drain Current ( Pulsed )	$T_C = 25\text{ }^\circ\text{C}, V_{GS} = 10\text{ V}$	-	8	A
$P_{tot}$	Drain power dissipation	$T_C = 25\text{ }^\circ\text{C}$	-	24	W
$T_{stg}$	Storage Temperature		-55	150	$^\circ\text{C}$
$T_J$	Junction Temperature		-	150	$^\circ\text{C}$
$I_S$	Continuous-Source Current	$T_C = 25\text{ }^\circ\text{C}$	-	6	A
$E_{AS}$	Single Pulsed Avalanche Energy	$V_{DD} = 50\text{ V}, L = 1.0\text{ mH}$	-	15.6	mJ
$R_{\theta JA}^*$	Thermal Resistance- Junction to Ambient		-	52	$^\circ\text{C/W}$
$R_{\theta JC}$	Thermal Resistance- Junction to Case		-	5.2	

Notes :

- \* Surface Mounted on 1 in<sup>2</sup> pad area,  $t \leq 10\text{ sec}$
- \*\* Pulse width  $\leq 300\text{ }\mu\text{s}$ , duty cycle  $\leq 2\%$
- \*\*\* Limited by bonding wire

## 5. Ordering Code

Product Name	Package	Reel Size	Tape width	Quantity	Note
LN3R88N200J	T0252			2500	

Note: COMTECH defines " Green " as lead-free ( RoHS compliant ) and halogen free ( Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC / JEDEC J-STD-020C )

## 6. Electrical Characteristics ( $T_A=25^\circ$ Unless Otherwise Noted )





Symbol	Parameter	Conditions	Min	Typ	Max	Unit
<b>Static Characteristics</b>						
$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_{DS} = 250\ \mu\text{A}$	200	-	-	V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_{DS} = 250\ \mu\text{A}$	2	-	4	V
$I_{DSS}$	Drain Leakage Current	$V_{DS} = 160\text{ V}, V_{GS} = 0\text{ V}$	-	-	1	$\mu\text{A}$
$I_{GSS}$	Gate Leakage Current	$V_{GS} = 0\text{ V}, V_{GS} = \pm 20\text{ V}$	-	-	$\pm 100$	nA
$R_{DS(ON)}^a$	On-State Resistance	$V_{GS} = 10\text{ V}, I_{DS} = 3\text{ A}$	-	388	430	m $\Omega$
		$V_{GS} = 6\text{ V}, I_{DS} = 2\text{ A}$	-	416	520	
<b>Diode Characteristics</b>						
$V_{SD}^a$	Diode Forward Voltage	$I_{SD} = 3\text{ A}, V_{GS} = 0\text{ V}$	-	-	1.3	V
$t_{rr}$	Reverse Recovery Time	$I_{DS} = 3\text{ A}, V_{GS} = 0\text{ V}$	-	44	-	nS
$Q_{rr}$	Reverse Recovery Charge	$dI_{SD}/dt = 100\text{ A}/\mu\text{s}$	-	96	-	nC
<b>Dynamic Characteristics<sup>b</sup></b>						
$C_{ISS}$	Input Capacitance	$V_{GS} = 0\text{ V}, V_{DS} = 100\text{ V}$ Frequency = 1 MHz	-	214	-	pF
$C_{OSS}$	Output Capacitance		-	18	-	
$C_{rSS}$	Reverse Transfer Capacitance		-	10	-	
$t_d(on)$	Turn-on Delay Time	$V_{DS} = 100\text{ V}, V_{GEN} = 10\text{ V},$ $R_G = 3.9\ \Omega, R_L = 33\ \Omega,$ $I_{DS} = 3\text{ A}$	-	4	-	nS
$t_r$	Turn-on Rise Time		-	3	-	
$t_d(off)$	Turn-off Delay Time		-	7.4	-	
$t_f$	Turn-off Fall Time		-	6.8	-	
<b>Gate Charge Characteristics<sup>b</sup></b>						
$Q_g$	Total Gate Charge	$V_{DS} = 100\text{ V}, V_{GS} = 10\text{ V},$ $I_{DS} = 3\text{ A}$	-	5	-	nC
$Q_{gs}$	Gate-Source Charge		-	1.8	-	
$Q_{gd}$	Gate-Drain Charge		-	1.4	-	

Notes :





a : Pulse test ; pulse width  $\leq 300\ \mu\text{s}$ , duty cycle  $\leq 2\%$

b : Guaranteed by design, not subject to production testing





## 7. Typical Characteristics



## 7. Typical Characteristics (cont.)




## 7. Typical Characteristics (cont.)



## 8. Package Dimensions

### T0252-3L



Symbol	Dimensions In Millimeters	
	MIN.	MAX.
A	2.19	2.38
A1	0.02	0.13
D	5.30	6.40
E	6.35	6.80
E1	5.20	5.50
c	0.40	0.60
c1	0.40	0.60
b	0.55	0.85
e	2.30BCS	
L	1.00	1.80
L1	0.70	1.80
L2	0.70BCS	
L3	2.40	2.80
H	9.20	10.40